


TUNING FORK CRYSTAL UNIT (SMD • Jacket Type)

RoHS Compliant Optional

CMJ206T


3000pcs/reel




FEATURES

- High-density mounting SMD with jacket.
- Automatic mounting and reflowable Type.
- Most appropriate for clock source for portable and other various equipment with low power consumption.

DIMENSION [mm]



SOLDER PAD LAYOUT [mm]



STANDARD SPECIFICATIONS

Item	Model	CMJ206T	Conditions
Nominal Frequency	f_0	32.768kHz	
Frequency Tolerance	$\Delta f/f_0$	$\pm 20 \text{ ppm}$	at 25°C
Load capacitance	C_L	12.5pF	Need to specify your requirement
Operating Temperature Range	T_{OPR}	$-40^\circ\text{C} \sim +85^\circ\text{C}$	
Storage Temperature Range	T_{STR}	$-55^\circ\text{C} \sim +125^\circ\text{C}$	
Turnover Temperature	T_M	$25^\circ\text{C} \pm 5^\circ\text{C}$	See figure 2 in P4
Temperature Coefficient	β	$-0.034 \pm 0.006 \text{ ppm}/^\circ\text{C}^2$	
Motional (series) resistance	R_1	50K Ω Max.	at 25°C
Level of drive	D_L	1 μW Max.	
Aging (first year)	$\Delta f/f_0$	$\pm 3 \text{ ppm}$ Max.	$25^\circ\text{C} \pm 3^\circ\text{C}$
Quality Factor	Q	70000 Typ.	
Shunt capacitance	C_0	1.35pF Typ.	